



# MODEL 2138 | Specification Sheet

Commercial Series • Low Voltage • Bollard

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	9 W Max.
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 16" H

## ORDERING INFORMATION

EXAMPLE: **BR-2138-CSN-4.5-W-36**

MOUNTING	MODEL	FINISH	LED
BR	2138		

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
BR ABS Ground Stake	2138	CSN Natural Copper	4.5-W-15 4.5 Watts   Warm   15° Narrow Spot	Fixtures shipped with specified mounting hardware.
		CSO Olde Copper	4.5-W-25 4.5 Watts   Warm   25° Spot	
		SS Stainless Steel	4.5-W-36 4.5 Watts   Warm   36° Flood	
			4.5-W-60 4.5 Watts   Warm   60° Wide Flood	
			5.5-W-15 5.5 Watts   Warm   15° Narrow Spot	
			5.5-W-25 5.5 Watts   Warm   25° Spot	
			5.5-W-36 5.5 Watts   Warm   36° Flood	
			5.5-W-60 5.5 Watts   Warm   60° Wide Flood	
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	NL No Lamp	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel post fitted with machined solid brass cap.

### FINISH:

Brushed Natural Copper, Olde Copper finish or Stainless Steel.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

Lens Cover also available in powder coat finish with the following standard colors:  
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),  
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),  
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),  
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

### LENS:

Clear, machined acrylic lens.

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### MOUNTING:

Aluminum mounting base with ABS ground stake included.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (**UL 1838**)
- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

## DIMENSIONS

