TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES

Wattage	9 W Max.
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Туре	MR-16 LED
Housing	Die-cast Aluminum
Dimensions	2%" DIA x 7%" D



EXAMPLE: **GR-2216-B-4.5-W-36-IK-FR**

ORDERING INFORMATION

MOUNTING MODEL FINISH LED KNUCKLE ACCESSORIES
2216 IK

мои	NTING	MODEL		FINIS	SH					
GR	ABS ground stake	2216		В	Black		BR	Architectural Brick	G	Verde
WR	Wall-mount canopy				Z Architectural Bronze		LZ	Light Bronze	P	Pewter
TR	Tree-mount junction box			DZ Dark Bronz		e S		Special Bronze	M	Mocha
				GТ	Granite		GG	Glossy Gray	OF	Olde Finish
				w	White		R	Rust		
							HG	Hunter Green		
							WB	Weathered Bronze		
							WI	Weathered Iron		
							GM	Graphite Metallic		
LED			KNUCKLE			ACC	ESSORIES		ORDERING	NOTES
4.5-W	15 4.5 Watts Warm 15° Na	rrow Spot	IK Infinity Knuckle w	with ½" NPT thread		FR	Frosted Lens		Fixtures shipped with specified mounting	
4.5-W	25 4.5 Watts Warm 25° Sp	ot				BL	Flat Cool Blue Le	ns	hardware.	
4.5-W	36 4.5 Watts Warm 36° Flo	4.5 Watts Warm 36° Flood				SL	Flat Spread Lens		If fixture is to be used in conjunction with	
4.5-W	60 4.5 Watts Warm 60° Wi	.5 Watts Warm 60° Wide Flood		DBL		Flat Dark Blue Lens		Extended Arm Mount (EAM): Must specify with extended wire length		
5.5-W	15 5.5 Watts Warm 15° Na	rrow Spot		GL F	Flat Dark Green I	ens				
5.5-W	25 5.5 Watts Warm 25° Sp	ot			RL FI	Flat Red Lens				
5.5-W	36 5.5 Watts Warm 36° Flo	ood				YL	Flat Amber Lens			
5.5-W	60 5.5 Watts Warm 60° Wi	de Flood				HL	Honeycomb louv	er		
	NL No Lamp					5	5' Wire Lead			



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, tempered glass lens. Optical effect lenses are available.

MOUNTING:

Infinity Knuckle – Die-cast, copper-free aluminum, stainless steel stem with $\frac{1}{2}$ " NPT thread. A fully sealed spherical grommet allows for precise aiming and retention.

FASTENERS/INSERTS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°) Narrow Spot **25** (25°) Medium Flood **36** (36°) Wide Flood **60** (60°)

DIMENSIONS





