



**MODEL 5275** | Specification Sheet  
Commercial Series • Low Voltage • In-Grade

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	9 W Max.
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 6¼" D

**ORDERING INFORMATION**

EXAMPLE: **GW-5275-BSN-4.5-W-36-CFR**

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
	5275			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
<b>GW</b> In-Grade <b>CM</b> In-Grade Conduit Mount	<b>5275</b>	<b>BSN</b> Natural Brass	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>CFR</b> Crowned Frosted Lens
		<b>BSO</b> Olde Brass	<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	<b>CBL</b> Crowned Cool Blue Lens
		<b>SS</b> Stainless Steel	<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	<b>SL</b> Flat Spread Lens
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	<b>DBL</b> Flat Dark Blue Lens
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	<b>GL</b> Flat Dark Green Lens
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	<b>RL</b> Flat Red Lens
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	<b>YL</b> Flat Amber Lens
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	<b>HL</b> Honeycomb louver
			<b>NL</b> No Lamp	
				<b>ORDERING NOTES</b>



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### LENS COVER CONSTRUCTION:

Machined Brass or 304 Stainless Steel.

### FINISH:

Natural Brass, Olde Brass or Natural Stainless Steel lens cover.  
Housing available in black only.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### OPTICS/AIMING:

Adjustable lamp bracket provides up to  $\pm 25^\circ$  of tilt as well as  $360^\circ$  rotation of housing for precise beam control. Lamp bracket can be locked into place to prevent disrupting lamp position when relamping.

### MOUNTING:

In-grade. Mounting accessories not required.  
Conduit mount fixtures have two  $\frac{3}{4}$ " NPT inlets on bottom.  
Optional concrete mounting kit available.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS:

UL Certified for wet locations (USA & Canada) | **(UL 1838)**

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### LIGHT DISTRIBUTION:

Very Narrow Spot **15** ( $15^\circ$ )  
Narrow Spot **25** ( $25^\circ$ )  
Medium Flood **36** ( $36^\circ$ )  
Wide Flood **60** ( $60^\circ$ )

## DIMENSIONS

