



**MODEL 1059** | Specification Sheet  
Commercial Series • Floodlight • LED

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	48 – 113 W
Voltage	120 – 277 VAC
Lumens	2460 – 10,700 Delivered Lumens
Distribution	NEMA type [H x V]: 2x2 (VNS), 2x2 (NS), 5x5 (MF), 6x6 (WF)
CCT	2700K, 3000K, 3500K, 4000K, 5000K
CRI	80 CRI min.
Dimming	0-10V or Phase Cut (TRIAC/ELV-120VAC only) available
Driver	Multi-Volt 120-277VAC with tri-modal dimming capabilities
Dimensions	10 <sup>1</sup> / <sub>8</sub> " W x 12 <sup>15</sup> / <sub>16</sub> " D x 9" DIA

**ORDERING INFORMATION**

EXAMPLE: 1059-GM-WF-27-D-MV-PCT-FS

**MODEL FINISH DISTRIBUTION COLOR TEMP LUMENS VOLTAGE DIMMING ACCESSORIES**  
1059 MV

MODEL	FINISH	DISTRIBUTION	COLOR TEMP	DELIVERED LUMENS	VOLTAGE	DIMMING	ACCESSORIES				
1059	<b>B</b> Black	<b>VNS</b> Very Narrow Spot	<b>27</b> 2700K	<b>B</b> 2460 Lumens	<b>MV</b> Multi Volt	<b>ND</b> Non Dimming	<b>BD</b> Barn Doors				
	<b>Z</b> Architectural Bronze			<b>C</b> 2793 Lumens							
	<b>DZ</b> Dark Bronze		<b>30</b> 3000K	<b>B</b> 2460 Lumens				<b>010</b> 0-10V	<b>FS</b> Full Light Shield		
	<b>GT</b> Granite										
	<b>W</b> White									<b>35</b> 3500K	<b>C</b> 2793 Lumens
	<b>BR</b> Architectural Brick										
	<b>LZ</b> Light Bronze	<b>40</b> 4000K	<b>H</b> 5887 Lumens	<b>PCT</b> Phase Cut (H, I Delivered Lumen Packages only)	<b>HS</b> Half Light Shield						
	<b>SB</b> Special Bronze					<b>50</b> 5000K	<b>I</b> 6416 Lumens				
	<b>GG</b> Glossy Gray	<b>NS</b> Narrow Spot	<b>27</b> 2700K					<b>D</b> 3199-3559 Lumens	<b>DF</b> Diffuse Filter		
	<b>R</b> Rust					<b>MF</b> Medium Flood	<b>E</b> 3476-3874 Lumens				
	<b>HG</b> Hunter Green	<b>30</b> 3000K	<b>F</b> 3933-4281 Lumens					<b>LSFH</b> Linear Spread Filter Horizontal			
	<b>WB</b> Weathered Bronze					<b>35</b> 3500K	<b>G</b> 4566-5181 Lumens				
	<b>WI</b> Weathered Iron	<b>40</b> 4000K	<b>D</b> 3199-3559 Lumens	<b>LSFV</b> Linear Spread Filter Vertical							
	<b>GM</b> Graphite Metallic				<b>50</b> 5000K	<b>E</b> 3476-3874 Lumens					
	<b>G</b> Verde	<b>WF</b> Wide Flood	<b>F</b> 3933-4281 Lumens								
	<b>P</b> Pewter			<b>30</b> 3000K	<b>G</b> 4566-5181 Lumens						
	<b>M</b> Mocha	<b>40</b> 4000K	<b>H</b> 9333-9550 Lumens								
	<b>OF</b> Olde Finish			<b>50</b> 5000K	<b>I</b> 10,301-10,708 Lumens						



**PROFESSIONAL OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



### SPECIFICATIONS

**HOUSING:**

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed. Housing aiming achieved via a heavy aluminum yoke strap and locked in position with stainless steel lock washers and nuts. Locking fasteners are covered with decorative die-cast aluminum end caps.

**DOOR:**

Die-cast A360 aluminum. Stainless steel fasteners. Door is designed to shed water from the lens surface.

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

**LENS:**

¼" thick tempered and beveled clear glass.

**REFLECTOR:**

Specular, semi-specular, or White Optic coated spun reflectors, anodized for maximum performance. Very Narrow Spot optic incorporates an additional internal source shield to eliminate unwanted glare outside the beam pattern.

**LED:**

Performance COB LEDs powered from 1050mA-2000mA.  
2460 – 10,700 Lumens delivered.  
48 – 113 Watts.

**COLOR TEMPERATURE:**

2700K, 3000K, 3500K, 4000K or 5000K CCT White.

**COLOR RENDERING:**

80 CRI minimum

**ACCESSORIES:**

Barn Doors, Full Shield, Half Shield, Diffuse Filter and Linear Spread Filter available.

**WIRING:**

- 18/3 SEOWW outdoor rated waterproof cable [for Non-dimmable and Phase Cut (TRIAC/ELV-120VAC only) options]
- 18/5 SJTOW outdoor rated waterproof cable [for 0-10V dimming option]

Cable exits fixture housing through a liquid tight cable fitting.

**MOUNTING:**

Yoke provided with ½ NPSM stainless Cord Seal Mount to secure the yoke strap directly into a ½-14 NPT threaded opening. See the Vista website for additional Mounts and Accessories.

**CERTIFICATIONS | STANDARDS | COMPLIANCE:**

- UL Certified for wet locations (USA & Canada) | (UL)
- Ingress Protection Rating: **IP66**
- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

**OPTICS/AIMING:**

NEMA defined floodlight optics. Housing aiming achieved via an aluminum yoke strap.


**DRIVER:**

Multi-Volt **MV** 120V-277V equipped with tri-modal dimming capabilities. Start up/Operating Temperature: -10°C to +50°C. Non-dimmable, 0-10V and Phase Cut (TRIAC/ELV-120VAC only) options available.

**LIGHT DISTRIBUTION:**

Very Narrow Spot **VNS** (NEMA 2H x 2V), Narrow Spot **NS** (NEMA 2H x 2V), Medium Flood **MF** (NEMA 5H x 5V), Wide Flood **WF** (NEMA 6H x 6V)

### DIMENSIONS





**DELIVERED LUMENS**

LUMEN PACKAGE	VNS	NS	MF	WF
<b>B</b>	60 Watts 2460 Lumens			
<b>C</b>	74 Watts 2793 Lumens			
<b>D</b>		48 Watts 3559 Lumens	48 Watts 3407 Lumens	48 Watts 3199 Lumens
<b>E</b>		50 Watts 3874 Lumens	50 Watts 3744 Lumens	49 Watts 3476 Lumens
<b>F</b>		60 Watts 4281 Lumens	60 Watts 4151 Lumens	59 Watts 3933 Lumens
<b>G</b>		74 Watts 5181 Lumens	74 Watts 4972 Lumens	74 Watts 4566 Lumens
<b>H</b>	96 Watts 5887 Lumens	96 Watts 9333 Lumens	96 Watts 9550 Lumens	95 Watts 9340 Lumens
<b>I</b>	112 Watts 6416 Lumens	113 Watts 10,360 Lumens	113 Watts 10,708 Lumens	112 Watts 10,301 Lumens

