



MODEL 5105 – BSO | Specification Sheet
Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE: MODEL:
PROJECT:

PRODUCT FEATURES



Wattage	2 – 4 W
Voltage	9 – 15 VAC
CCT	3000K, 4000K, 5000K
Housing	Die-cast Brass
Dimensions	3¼" W x 3" H x 2" D



ORDERING INFORMATION

EXAMPLE: GR-5105-BSO-2-W-FR

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	ACCESSORIES
GR	5105	BSO			

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	ACCESSORIES
GR ABS Ground Stake	5105	BSO Olde Brass	2 2 Watts 3 3 Watts 4 4 Watts	W 3000K N 4000K C 5000K	FR Frosted Lens 5 5' Wire Lead ORDERING NOTES Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length





SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast Brass.

FINISH:

Olde Brass.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Certified for wet locations (USA & Canada) | (UL 1838)

LED:

Performance LED.
2 – 4 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

